

Distributor Specs

Opel Distributor Specs

Opel Distributor Specifications for 1968 thru 1975 1900 cc Engines

1968		\$ 251,567,000
1969	Other Taxes To-Go	\$ 251,567,000
1969	Other Taxes To-Go	\$ 251,567,000
1969	Ad after 6-0-6	\$ 251,567,000
1970-71		\$ 251,567,000
1970	Manual Transmission	\$ 251,576,012
1970	Automatic Transmission	\$ 251,576,011
1970		\$ 251,576,012
1970		\$ 251,576,012
1970		\$ 251,576,189

NOTE - FOR ENGINE RPM & DEGREE, MULTIPLY APPLICATION BY 1

Model Number	4 th Digital Subchannel (Digital, Diagonal & RPS)				15 th Broadcast Channel (Digital, Diagonal & In. of Dig)			
	Diagonal	RPS	Digital	RPS	Diagonal	RPS	Digital	In. of Dig
2100 (2100-01)	400-500	5.5:7.5	150	15.5:18.5	1600	1600	1600	1600
2100 (2100-02)	400-500	5.5:7.5	150	15.5:18.5	1600	1600	1600	1600
2100 (2100-03)	400-500	5.5:7.5	150	15.5:18.5	1600	1600	1600	1600
2100 (2100-04)	400-500	5.5:7.5	150	15.5:18.5	1600	1600	1600	1600
2100 (2100-05)	400-500	5.5:7.5	150	15.5:18.5	1600	1600	1600	1600
2100 (2100-06)	400-500	5.5:7.5	150	15.5:18.5	1600	1600	1600	1600
2100 (2100-07)	400-500	5.5:7.5	150	15.5:18.5	1600	1600	1600	1600
2100 (2100-08)	400-500	5.5:7.5	150	15.5:18.5	1600	1600	1600	1600
2100 (2100-09)	400-500	5.5:7.5	150	15.5:18.5	1600	1600	1600	1600
2100 (2100-10)	400-500	5.5:7.5	150	15.5:18.5	1600	1600	1600	1600
2100 (2100-11)	400-500	5.5:7.5	150	15.5:18.5	1600	1600	1600	1600
2100 (2100-12)	400-500	5.5:7.5	150	15.5:18.5	1600	1600	1600	1600
2100 (2100-13)	400-500	5.5:7.5	150	15.5:18.5	1600	1600	1600	1600
2100 (2100-14)	400-500	5.5:7.5	150	15.5:18.5	1600	1600	1600	1600
2100 (2100-15)	400-500	5.5:7.5	150	15.5:18.5	1600	1600	1600	1600
2100 (2100-16)	400-500	5.5:7.5	150	15.5:18.5	1600	1600	1600	1600
2100 (2100-17)	400-500	5.5:7.5	150	15.5:18.5	1600	1600	1600	1600
2100 (2100-18)	400-500	5.5:7.5	150	15.5:18.5	1600	1600	1600	1600
2100 (2100-19)	400-500	5.5:7.5	150	15.5:18.5	1600	1600	1600	1600
2100 (2100-20)	400-500	5.5:7.5	150	15.5:18.5	1600	1600	1600	1600
2100 (2100-21)	400-500	5.5:7.5	150	15.5:18.5	1600	1600	1600	1600
2100 (2100-22)	400-500	5.5:7.5	150	15.5:18.5	1600	1600	1600	1600
2100 (2100-23)	400-500	5.5:7.5	150	15.5:18.5	1600	1600	1600	1600
2100 (2100-24)	400-500	5.5:7.5	150	15.5:18.5	1600	1600	1600	1600
2100 (2100-25)	400-500	5.5:7.5	150	15.5:18.5	1600	1600	1600	1600
2100 (2100-26)	400-500	5.5:7.5	150	15.5:18.5	1600	1600	1600	1600
2100 (2100-27)	400-500	5.5:7.5	150	15.5:18.5	1600	1600	1600	1600
2100 (2100-28)	400-500	5.5:7.5	150	15.5:18.5	1600	1600	1600	1600
2100 (2100-29)	400-500	5.5:7.5	150	15.5:18.5	1600	1600	1600	1600
2100 (2100-30)	400-500	5.5:7.5	150	15.5:18.5	1600	1600	1600	1600
2100 (2100-31)	400-500	5.5:7.5	150	15.5:18.5	1600	1600	1600	1600
2100 (2100-32)	400-500	5.5:7.5	150	15.5:18.5	1600	1600	1600	1600
2100 (2100-33)	400-500	5.5:7.5	150	15.5:18.5	1600	1600	1600	1600
2100 (2100-34)	400-500	5.5:7.5	150	15.5:18.5	1600	1600	1600	1600
2100 (2100-35)	400-500	5.5:7.5	150	15.5:18.5	1600	1600	1600	1600
2100 (2100-36)	400-500	5.5:7.5	150	15.5:18.5	1600	1600	1600	1600
2100 (2100-37)	400-500	5.5:7.5	150	15.5:18.5	1600	1600	1600	1600
2100 (2100-38)	400-500	5.5:7.5	150	15.5:18.5	1600	1600	1600	1600
2100 (2100-39)	400-500	5.5:7.5	150	15.5:18.5	1600	1600	1600	1600
2100 (2100-40)	400-500	5.5:7.5	150	15.5:18.5	1600	1600	1600	1600
2100 (2100-41)	400-500	5.5:7.5	150	15.5:18.5	1600	1600	1600	1600
2100 (2100-42)	400-500	5.5:7.5	150	15.5:18.5	1600	1600	1600	1600
2100 (2100-43)	400-500	5.5:7.5	150	15.5:18.5	1600	1600	1600	1600
2100 (2100-44)	400-500	5.5:7.5	150	15.5:18.5	1600	1600	1600	1600
2100 (2100-45)	400-500	5.5:7.5	150	15.5:18.5	1600	1600	1600	1600
2100 (2100-46)	400-500	5.5:7.5	150	15.5:18.5	1600	1600	1600	1600
2100 (2100-47)	400-500	5.5:7.5	150	15.5:18.5	1600	1600	1600	1600
2100 (2100-48)	400-500	5.5:7.5	150	15.5:18.5	1600	1600	1600	1600
2100 (2100-49)	400-500	5.5:7.5	150	15.5:18.5	1600	1600	1600	1600
2100 (2100-50)	400-500	5.5:7.5	150	15.5:18.5	1600	1600	1600	1600
2100 (2100-51)	400-500	5.5:7.5	150	15.5:18.5	1600	1600	1600	1600
2100 (2100-52)	400-500	5.5:7.5	150	15.5:18.5	1600	1600	1600	1600
2100 (2100-53)	400-500	5.5:7.5	150	15.5:18.5	1600	1600	1600	1600
2100 (2100-54)	400-500	5.5:7.5	150	15.5:18.5	1600	1600	1600	1600
2100 (2100-55)	400-500	5.5:7.5	150	15.5:18.5	1600	1600	1600	1600
2100 (2100-56)	400-500	5.5:7.5	150	15.5:18.5	1600	1600	1600	1600
2100 (2100-57)	400-500	5.5:7.5	150	15.5:18.5	1600	1600	1600	1600
2100 (2100-58)	400-500	5.5:7.5	150	15.5:18.5	1600	1600	1600	1600
2100 (2100-59)	400-500	5.5:7.5	150	15.5:18.5	1600	1600	1600	1600
2100 (2100-60)	400-500	5.5:7.5	150	15.5:18.5	1600	1600	1600	1600
2100 (2100-61)	400-500	5.5:7.5	150	15.5:18.5	1600	1600	1600	1600
2100 (2100-62)	400-500	5.5:7.5	150	15.5:18.5	1600	1600	1600	1600
2100 (2100-63)	400-500	5.5:7.5	150	15.5:18.5	1600	1600	1600	1600
2100 (2100-64)	400-500	5.5:7.5	150	15.5:18.5	1600	1600	1600	1600
2100 (2100-65)	400-500	5.5:7.5	150	15.5:18.5	1600	1600	1600	1600
2100 (2100-66)	400-500	5.5:7.5	150	15.5:18.5	1600	1600	1600	1600
2100 (2100-67)	400-500	5.5:7.5	150	15.5:18.5	1600	1600	1600	1600
2100 (2100-68)	400-500	5.5:7.5	150	15.5:18.5	1600	1600	1600	1600
2100 (2100-69)	400-500	5.5:7.5	150	15.5:18.5	1600	1600	1600	1600
2100 (2100-70)	400-500	5.5:7.5	150	15.5:18.5	1600	1600	1600	1600
2100 (2100-71)	400-500	5.5:7.5	150	15.5:18.5	1600	1600	1600	1600
2100 (2100-72)	400-500	5.5:7.5	150	15.5:18.5	1600	1600	1600	1600
2100 (2100-73)	400-500	5.5:7.5	150	15.5:18.5	1600	1600	1600	1600
2100 (2100-74)	400-500	5.5:7.5	150	15.5:18.5	1600	1600	1600	1600
2100 (2100-75)	400-500	5.5:7.5	150	15.5:18.5	1600	1600	1600	1600
2100 (2100-76)	400-500	5.5:7.5	150	15.5:18.5	1600	1600	1600	1600
2100 (2100-77)	400-500	5.5:7.5	150	15.5:18.5	1600	1600	1600	1600
2100 (2100-78)	400-500	5.5:7.5	150	15.5:18.5	1600	1600	1600	1600
2100 (2100-79)	400-500	5.5:7.5	150	15.5:18.5	1600	1600	1600	1600
2100 (2100-80)	400-500	5.5:7.5	150	15.5:18.5	1600	1600	1600	1600
2100 (2100-81)	400-500	5.5:7.5	150	15.5:18.5	1600	1600	1600	1600
2100 (2100-82)	400-500	5.5:7.5	150	15.5:18.5	1600	1600	1600	1600
2100 (2100-83)	400-500	5.5:7.5	150	15.5:18.5	1600	1600	1600	1600
2100 (2100-84)	400-500	5.5:7.5	150	15.5:18.5	1600	1600	1600	1600
2100 (2100-85)	400-500	5.5:7.5	150	15.5:18.5	1600	1600	1600	1600
2100 (2100-86)	400-500	5.5:7.5	150	15.5:18.5	1600	1600	1600	1600
2100 (2100-87)	400-500	5.5:7.5	150	15.5:18.5	1600	1600	1600	1600
2100 (2100-88)	400-500	5.5:7.5	150	15.5:18.5	1600	1600	1600	1600
2100 (2100-89)	400-500	5.5:7.5	150	15.5:18.5	1600	1600	1600	1600
2100 (2100-90)	400-500	5.5:7.5	150	15.5:18.5	1600	1600	1600	1600
2100 (2100-91)	400-500	5.5:7.5	150	15.5:18.5	1600	1600	1600	1600
2100 (2100-92)	400-500	5.5:7.5	150	15.5:18.5	1600	1600	1600	1600
2100 (2100-93)	400-500	5.5:7.5	150	15.5:18.5	1600	1600	1600	1600
2100 (2100-94)	400-500	5.5:7.5	150	15.5:18.5	1600	1600	1600	1600
2100 (2100-95)	400-500	5.5:7.5	150	15.5:18.5	1600	1600	1600	1600
2100 (2100-96)	400-500	5.5:7.5	150	15.5:18.5	1600	1600	1600	1600
2100 (2100-97)	400-500	5.5:7.5	150	15.5:18.5	1600	1600	1600	1600
2100 (2100-98)	400-500	5.5:7.5	150	15.5:18.5	1600	1600	1600	1600
2100 (2100-99)	400-500	5.5:7.5	150	15.5:18.5	1600	1600	1600	1600
2100 (2100-100)	400-500	5.5:7.5	150	15.5:18.5	1600	1600	1600	1600

^a Vacuum reduced 4–5 deg. (i) closed circuit.

1973 Book: *Classifier Specification*

Branch Part No.	Accessories Related to No. of Hg.	
	Drop	In. Hg.
4711-176012	2.5	2.4-4

Point Cup	
1971-72	916"
1973	916"
1975	916"

Source: AMERICAN LIBRARY, (1993)

Gary